

Advantages

- + Will not shrink, crack or slump
- + No thickness limitation
- + No flashing or grinning
- + Lump free easy mix
- + Easy to apply
- + Easy to sand
- + White



ENDUITS DE PEINTURE
NF 446

www.ecolabels.fr



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



INTERIOR FILLER

GENERAL INFORMATION

Description

Powder filler

Intended use

- Interior
- Filling holes and cracks

Manual application



Use



interior

Application thickness



Any thickness

Working time



35 min

Dilution



0,50L

1 kg

USE

DILUTION 50% - i.e. 0,50 liter of water per 1 kg of powder

PREPARATION Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

APPLICATION

Conditions Do not apply at temperatures of below + 8°C or above + 35°C, or at a relative humidity above 70% H.R

Equipment Filling knife, blade

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS Any thickness

AVERAGE CONSUMPTION 1 kg of powder fills a volume of 1 liter


SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, filler, conventional paint, light-weight wall coverings.



INTERIOR FILLER

TECHNICAL DATA

COMPONANTS	Plaster base coat mix, organic binder, mineral fillers, additives 99% of raw materials of natural origin (Natural plaster, calcium carbonate, gypsum, gelatin, starch)
pH	7 ± 0.5
COLOUR	White
WORKING TIME AT 20°C	Approximately 35 minutes
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 3
NORM	NF EN 16566 NF ENVIRONNEMENT : Enduits de peinture - NF 446 The certified characteristics are available from AFNOR Certification 11 rue de Pressensé 93571 La Plaine Saint-Denis Cedex - France or on www.ecolabels.fr
V.O.C.	< 0,1 g/l (ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Do not breathe dust. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	2 kg and 1 kg box - 6 kg bag
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu