

PRESTONETT

THE SOLUTION TO SUBSTRATE REPAIRS

MANUALLY APPLIED INTERIOR & EXTERIOR FILLERS

Beissier
Applying excellence

PRESTONETT

WATERPROOF MASONRY FILLER

30% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Waterproofing, filling & finishing masonry substrate
- Repairing and shaping windows sills & mouldings

Advantages

- + Fills up to 15 mm in 1 application
- + Can be applied on damp substrates
- + Waterproof after 3 mm thickness
- + Resistant to saltpeter and seawater
- + Repairs reinforced concrete, providing protection against carbonation process
- + Flexible
- + Easy to mix and apply
- + Water vapour permeable
- + Grey

1 kg 6 kg

PRESTONETT

EXTERIOR QUICK DRY FILLER

25% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes and cracks of up to 4 cm
- Renovation work

Advantages

- + Excellent adhesion to substrates
- + Can be overcoated after just 3 hours
- + Does not shrink or crack
- + Water vapour permeable
- + Can be applied to damp substrates
- + Fibre enriched
- + Lump free mixing
- + Sameday = apply, sand & paint
- + White

1 kg 6 kg

WWW.BEISSIER.EU
Stay connected!

FOLLOW US ON

Beissier
Applying excellence

BEISSIER
Becket House
1 Lambeth Palace Road
London SE1 7EU

020 7092 6696
contact@beissier.eu

PRESTONETT

INTERIOR FILLER

99% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes and cracks

Advantages

- + Will not shrink, crack or slump
- + No thickness limitation
- + No flashing or grinning
- + Lump free easy mix
- + Easy to apply
- + Easy to sand
- + White

1 kg 2 kg 6 kg

PRESTONETT

READY MIXED FILLER

78% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling small holes and cracks

Advantages

- + Excellent adhesion to substrates
- + Easy to apply
- + Dries hard
- + Easy to sand
- + Will not flash or grin
- + No need to spot prime

1 kg

PRESTONETT

QUICK DRY FILLER

80% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Minor surface repairs

Advantages

- + Ready to sand & paint in 15 min
- + Excellent adhesion to substrates
- + Water and humidity resistant
- + White

200 ml

PRESTONETT

LIGHT WEIGHT FILLER

80% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes and cracks of all sizes

Advantages

- + Excellent adhesion to substrates
- + Fills & finishes in a single pass
- + No thickness limitations
- + Very easy to sand
- + Does not shrink or crack
- + Very fine finish
- + Brilliant white

250 ml 750 ml

PRESTONETT

MULTIPURPOSE FILLER

20% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes and cracks
- Levelling and finishing surfaces
- Taping and jointing plasterboards
- Coving adhesive

Advantages

- + The «All-in-one» for internal repairs
- + Fills up to 5 cm in 1 application
- + Will not shrink, crack or slump
- + No flashing or grinning
- + Easy to mix & easy to apply
- + Easy to sand
- + Brilliant white

1 kg 5 kg

PRESTONETT

MULTI-LIGHT FILLER

90% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Taping & jointing plasterboard
- Filling small holes and cracks
- Skim coating

Advantages

- + 4 IN 1
 - Plasterboard jointing compound
 - Filling up to 8 mm
 - Crack repair
 - Levelling block work
 - Skim coating surfaces
- + Application
 - Very smooth application
 - Light weight
 - Apply with roller, trowel or blade
- + Easy to sand
- + Fine finish
- + White

4 kg 12 kg



PRESTONETT

FINE SURFACE FILLER

96% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Finishing substrates
- Allows to hide small defects

Advantages

- + Very fine finish
- + Excellent adhesion to substrates
- + No need to spot prime
- + Enhances the paint finish
- + Smooth application, easy sand
- + Over coat after 4 hours
- + Will not flash or grin
- + White

1 kg

PRESTONETT

FLEXIBLE CRACK REPAIR FILLER

70% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Repairs to reoccurring cracks due to structural movement

Advantages

- + Highly flexible
- + Excellent adhesion to substrates
- + Fibre reinforced for moving cracks
- + Waterproof
- + No fibre tape or fabric required
- + White

600 ml

PRESTONETT

WOOD REPAIR FILLER

96% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes & cracks in all types of woodwork
- Reconstitute missing wood due to decay

Advantages

- + Easy to mix
- + Excellent adhesion to substrates
- + Very hard when dry
- + Ideal for repairing broken angles
- + Can be carved, drilled and painted
- + Can be tinted with a water based dye
- + Can be painted, stained, varnished and waxed
- + Easy to sand
- + Fine finish
- + White

1 kg

PRESTONETT

WOOD FILLER

78% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling small holes and cracks
- Repairing minor imperfections

Advantages

- + 2 in 1 - Fill & skim
- + Easy to apply
- + Excellent adhesion to substrates
- + Easy to sand
- + Fine finish

1 kg

PRESTONETT

WOOD FILLER TUBE

78% OF RAW MATERIALS OF NATURAL ORIGIN

Advantages

- Filling holes & cracks on doors, window frames, skirting boards & floor boards

Advantages

- + Flexible
- + Fibre glass reinforced
- + Quick drying
- + Easy to apply & sand
- + Suitable for use on most types of wood

125 ml

WHITE
NATURAL
MEDIUM
DARK



| | FILLERS | | | | | | | | | | | | | |
|------------------------------------|---|--|---|-----------------------|---------------------------------|---------------------------------|---------------------|-----------------------|------------------------------|------------------------------|--|---------------------------|---|-------------|
| | WATERPROOF MASONRY FILLER | EXTERIOR QUICK DRY FILLER | INTERIOR FILLER | READY MIXED FILLER | QUICK DRY FILLER | LIGHT WEIGHT FILLER | MULTIPURPOSE FILLER | MULTI-LIGHT FILLER | FINE SURFACE FILLER | FLEXIBLE CRACK REPAIR FILLER | WOOD REPAIR FILLER | WOOD FILLER | WOOD FILLER TUBE | |
| | | | | | | | | | | | | | | |
| | POWDER | POWDER | POWDER | READY MIXED | READY MIXED | POWDER | POWDER | READY MIXED | READY MIXED | POWDER | POWDER | READY MIXED | READY MIXED | |
| | | | | | | | | | | | | | | |
| USE | | | | | | | | | | | | | | |
| Filling Holes and cracks | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | ■ | ■ | ■ | ■ | |
| Repair (shaping, moulding, etc.) | ■ | | | | | | | | | | ■ | | | |
| Fixing cornices, plaster mouldings | | | | | | | ■ | | | | | | | |
| Taping and Jointing | | | | | | | ■ | ■ | | | | | | |
| Levelling | ■ | | | | | | ■ | ■ | | | | | | |
| Skim-coating | | | | | | | ■ | ■ | ■ | | | | | |
| Others uses | Waterproofing Reinforced concrete repair | Renovation work | | | | | | | Allows to hide small defects | | Reconstitute missing wood | Repair minor imperfection | Special woods Suitable for use on floor boards | |
| SUBSTRATES* | | | | | | | | | | | | | | |
| Concrete | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | |
| Cellular concrete | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | ■ | | | | |
| Brick | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | ■ | | | | |
| Concrete Block | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | ■ | | | | |
| Cement | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | |
| Plaster | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | |
| Plasterboard | | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | |
| Stone | ■ | ■ | | | | | ■ | | | | | | | |
| Mortars | ■ | ■ | | | | | ■ | | | | | | | |
| Primed wood | | | | | | ■ | | | ■ | ■ | | | | |
| Old sprinkle effect | | | | | | | ■ | ■ | | | | | | |
| Old painted substrates | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | |
| Glass cloth | | | | | | | ■ | ■ | | | | | | |
| Wood, chipboard, plywood... | | | | | | | | | | | ■ | ■ | ■ | |
| OVERCOAT | | | | | | | | | | | | | | |
| Primer | ■ | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | |
| Interior conventional paint | ■ | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | |
| Light-weight wall coverings | ■ | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | |
| Wood stains | | | | | | | | | | | ■ | ■ | ■ | |
| Varnishes | | | | | | | | | | | ■ | ■ | ■ | |
| Exterior conventional paint | ■ | ■ | | ■ | ■ | ■ | | | | ■ | ■ | ■ | ■ | |
| Epoxyde, polyurethane | | ■ | | | | | | | | | | | | |
| TECHNICAL DATA | | | | | | | | | | | | | | |
| Dilution rate | 25% | 45% | 50% | Ready Mixed | Ready Mixed | Ready Mixed | 50% | Ready Mixed | Ready Mixed | Ready Mixed | Ready Mixed | 50% | Ready Mixed | Ready mixed |
| Maximum application Thickness | 15 mm | 40 mm | Any thickness | 10 mm | 3 mm | Any Thickness | 50 mm | 8 mm | 1 mm | 3 mm | Any thickness | 10 mm | 5 mm | |
| Working Time | 30 min | 35 min | 35 min | No limit | No limit | No limit | 60 min | No limit | No limit | No limit | 35 min | No limit | No limit | |
| Average Consumption | 1,2 kg/m ² | 0,9 kg of powder fills a volume of 1 litre | 1kg of powder fills a volume of 1 litre | 0,5 kg/m ² | 1L/m ² /mm thickness | 1L/m ² /mm thickness | 1 kg/m ² | 1,3 kg/m ² | 0,25 kg/m ² | 1L/mm/m ² | 1 kg of powder fills a volume of 1 litre | 0,5 kg/m ² | 1,4 kg/m ² | |
| Colour | Grey | White | White | White | White | White | White | White | White | White | White | Beige | White, Natural, Medium, Dark | |
| Equipment | | | | | | | | | | | | | | |

* Substrates must be hard, cohesive, clean, sand and dry. (Except for Masonry Filler and Exterior Quick Dry Filler. They can be applied on damp substrates.) Refer to the data sheets or the FDS for all complementary information.

